

Standard Concrete Masonry Units

	Standard	Half High	Half	Corner	Semi-Solid	Bond Beam Lintel	High Lintel	KO Bond Beam	Single Bullnose	Single Bullnose	Double Bullnose	Double Bullnose	Single Score	Single Score	Three Score	
Metric Heavy Weight Units	100 mm 100 mm Standard w Breaker 90 W 190 H 390 L	100 mm 100 mm Half High 90 W 90 H 390 L	100 mm 100 mm Half 90 W 190 H 190 L	100 mm 100 mm L-Corner Return 90/190 W 190 H 390 L					100 mm Single Bullnose w Breaker 90 W 190 H 390 L	Half		Half	100 mm Single Score 90 W 190 H 390 L	2 Sides		
	150 mm 150 mm Standard w Breaker 140 W 190 H 390 L	150 mm 150 mm Half High 140 W 90 H 390 L	150 mm 150 mm Half 140 W 190 H 190 L		150 mm Semi Solid 2 Hr Fire Rating 140 W 190 H 390 L	150 mm Bond Beam Lintel 140 W 190 H 390 L			150 mm Single Bullnose w Breaker 140 W 190 H 390 L		150 mm Double Bullnose w Breaker 140 W 190 H 390 L					
	200 mm 200 mm Standard & Sash End 190 W 190 H 390 L	200 mm 200 mm Half High 190 W 90 H 390 L	200 mm 200 mm Half Sash End 190 W 190 H 190 L	200 mm 45° Corner 190 W 190 H 337 L	200 mm O Block 190 W 190 H 390 L	200 mm Bond Beam Lintel 190 W 190 H 390 L	200 mm Full Beam Lintel 190 W 390 H 190 L	200 mm Knock Out Lintel 190 W 190 H 390 L	200 mm Single Bullnose w Breaker 190 W 190 H 390 L	200 mm Single Bullnose Half 190 W 190 H 390 L	200 mm Double Bullnose w Breaker 190 W 190 H 390 L	200 mm Double Bullnose Half 190 W 190 H 390 L	200 mm Single Score 190 W 190 H 390 L	200 mm Single Score 2 Sides 190 W 190 H 390 L	200 mm Three Score 190 W 190 H 390 L	
	250 mm 250 mm Standard & Sash End 240 W 190 H 390 L	250 mm 250 mm Half High 240 W 90 H 390 L	250 mm 250 mm Half Sash End 240 W 190 H 190 L	250 mm L-Corner Return 240 W 190 H 390 L	250 mm O Block 240 W 190 H 390 L	250 mm Bond Beam Lintel 240 W 190 H 390 L			250 mm Single Bullnose w Breaker 240 W 190 H 390 L		250 mm Double Bullnose w Breaker 240 W 190 H 390 L		250 mm Single Score 240 W 190 H 390 L			
300 mm 300 mm Standard & Sash End 290 W 190 H 390 L		300 mm 300 mm Half No Sash 290 W 190 H 190 L														

	Standard	Semi-Solid	Half
Metric Exterior Grade Units*	100 mm 100 mm Standard 90 W 190 H 390 L		
	200 mm 200 mm Standard & Sash End 190 W 190 H 390 L	200 mm 200 mm Semi Solid 4 hr Fire Rating 190 W 190 H 390 L	200 mm 200 mm Half Sash End 190 W 190 H 190 L
	250 mm 250 mm Standard & Sash End 240 W 190 H 390 L		Chimney Block 390 W 190 H 390 L
	300 mm 300 mm Standard & Sash End 290 W 190 H 390 L		

	Standard	Semi-Solid	Half
Metric Light Weight Units	150 mm 150 mm Standard w Breaker 140 W 190 H 390 L		
	200 mm 200 mm Standard & Sash End 190 W 190 H 390 L	200 mm 200 mm Semi Solid 4 hr Fire Rating 190 W 190 H 390 L	200 mm 200 mm Half Sash End 190 W 190 H 190 L
	250 mm 250 mm Standard & Sash End 240 W 190 H 390 L		Chimney Block 390 W 190 H 390 L
	300 mm 300 mm Standard & Sash End 290 W 190 H 390 L		

